

Neon Flex Specification





N012120BB1LZ(N1222)-Arc

N012120BC1LZ(N1222)-Arc



Product Parameter

- 12x22 arc surface neon flex led strip, can bend left and right;
- Light source: highlights LED chips;
- Craft material: high -light transmission and environmental -friendly silicone material, good flexibility of silicone material;
- Optical design: Unique optical light structure design, uniform light on the surface, no shadow, no light spots, very soft light;
- Exterior design: simple and fashionable, exquisite and unique brings better lighting performance to indoor/outside applications;
- Product certification: UL, CE, RoHS;
- Environmental characteristics: salt tolerance, corrosion resistance, flame retardant, UV resistance;
- Work / storage temperature: TA: -25 ~ 55 °C / 0 °C ~ 60 °C;
- Product application: signature lighting, outdoor/interior decoration, architectural contour application;
- 2 years of quality insurance, working life ≥36000 hours.




Photoelectric parameters

PN	Color	CCT	LED Qty/M	Pixel/M	Cutting Length	Voltage	Power	Luminance (lm/m)	Standard Length	Max Length
N012120BB1LZ (N1222)-Arc	W	3000K	SMD5050 120PCS/m	/	25mm	DC12V	12W/m	W:390lm	5025 ±15mm	15m
N012120BC1LZ (N1222)-Arc		4000K			50mm	DC24V				
		6500K								

Remarks:

1. The above parameters are tested based on 1M standard products;
2. The luminous flux is allowed to have an error range of ±10%;
3. The above parameters are typical values;
4. When this neon led is longer than 5 meters, it needs power from both ends;
5. Subject to change without prior notice.
- 6.Length tolerance applies. Actual product dimensions may vary.

Product light distribution curve



Luminous output: 78.83Lm

1m	10.58, 32.85lx	296.59cm
2m	2.646, 8.214lx	593.18cm
3m	1.176, 3.651lx	889.77cm
4m	0.6614, 2.053lx	1186.36cm
5m	0.4233, 1.314lx	1482.95cm
6m	0.2940, 0.9126lx	1779.54cm
7m	0.2160, 0.6705lx	2076.13cm
8m	0.1653, 0.5134lx	2372.72cm
9m	0.1306, 0.4056lx	2669.31cm
10m	0.1058, 0.3285lx	2965.89cm

Height Eavg, Emax Angle: 112.01° Diameter


Note: the curve is the illumination area and the average illumination within the area of the lamp under different projection distance

Effective average illumination




Mechanical parameters

mold injection end cap
- Straight outlet


Unit: mm/in



12V/24V
GND






mold injection end cap - side outlet



Left outlet Right outlet

Right outgoing line (according to the male input)


12V/24V
GND




Note: Length tolerance applies. Actual product dimensions may vary.

1222 Installation diagram

Wipe the dust on the installation luminous surface with clean water.





First fix the buckle with screws, and then clip the neon light strip into the buckle. When the length of the neon light strip is greater than 2 meters, two people are required to install it together. (refer to the figure below)




Overall dimension of buckle: L30*W11.4*H18.1mm




L1.181*W0.452*H0.712in




Surface




When the length of neon light strip is more than 2 meters, two people are required to install it together.



Surface



Mounted embedded




Mounted embedded

Overall dimension of aluminum profile: L30*W11.4*H18.1mm


L39.37*W0.452*H0.712in

Correct installation method


①









②




③



Error installation method







Cutting and the waterproof treatment of both ends

By default, our products will be shipped in regular lengths according to customer requirements.


If the customer has to cut and assemble on site, we can provide some end caps with holes and end caps without holes (all sections can be used). However, please note that in this case, the front and rear ends must be glued for waterproof treatment.




Cutting precautions

Waterproof treatment after cutting

1. The cut output end is glued and plugged with a non hole end cap (Fig. 1);
2. If there is no welding cable at the head and tail ends after cutting, first thread the male wire through the end cap, then weld it to the head end of the LED neon flex, and then apply glue for waterproof treatment (Fig. 2);
3. If there is no cable at the input end of cutting, and the male input cable must be welded (Fig. 3).




Connection diagram



matters needing attention

- Please use DC12V or DC24V isolation power supply according to the actual LED light strip, and the ripple of the constant voltage source is less than 5%. The LED light bar can not be used to use the resistance to lower voltage pressure, non-isolation and other types of power supply.
- In practical application, the power supply should reserve 20% margin (it is recommended to use only 80% power) to ensure sufficient voltage to drive products.
- Please operate carefully. When the power is connected, do not touch the AC power terminal to prevent electric shock.
- Pay attention to the positive and negative poles of the power line. Do not connect them incorrectly. Check whether the voltage of the power supply is consistent with that of the product to avoid product damage.
- Please avoid scratching, twisting and irregular bending of the product during installation, otherwise it may cause irreparable damage to the product.
- In order to ensure the service life and reliability of the led neon flex, please do not bend in the arc with a radius of less than 80 mm. Too small bending radius will damage the product itself.
- If the actual application length exceeds the specified length, it will lead to overload, heating, uneven brightness and other phenomena.
- In order to protect your eyes from injury, try to avoid staring at the luminous surface of the led neon flex for a long time.
- Non professional personnel are forbidden to install, disassemble and repair the product.
- It is strictly prohibited to use any acidic or alkaline adhesive to fix the product (including but not limited to glass adhesive, etc.).
- The use scenarios of different IP grades of products are different, and IP67 is not suitable for immersion environment.
- Due to structural differences of products with different sizes and specifications under the same color temperature value, the final color of the product is slightly deviated, which shall be confirmed before use.
- Please use professional cutting tools when cutting.


Product Accessories

Name	Describe	Picture	Net weight (g)	Product size (mm)	Remarks
Alum LED Profile	Pre installation slot		105g	L1000xW11.4xH18.1	Aluminum
Alum LED Profile	Pre installation slot		3.23g	L30xW11.4xH18.1	Aluminum
Modeling carrier	Shapable mounting slot		375g	L5000xW11xH15	Stainless steel
Straight outlet end cap	Silicone front outlet end cap		2.5g	L14xW13xH25	Silicone
Side outlet end cap	Silicone side outlet end cap		2.7g	L17xW14.5xH25	Silicone
Seal the end cap	Silicone sealing end cap		2.17g	L14xW14xH25	Silicone
Filling glue	300h mono molecular silica gel		125g	L32xW46xH17	Liquid glue
Female Connector	3PIN connector		23g	φ 15xL200	Silicone
Male Connector	3PIN Connector		18g	φ 15xL200	Silicone
Connector	3PIN IP65 Connector		/	/	Extension cord
Power supply	240W waterproof power supply		1.38Kg	L244.2xW68xH38.8	/
Power supply	350W Non-waterproof power supply		0.82Kg	L215xW115xH30	/
Power supply	400W rainproof power supply		1.23Kg	L220.4xW130xH48	/

Product packaging

· Standard packaging

1.For carton packaging, the line label is pasted 80mm away from the end of the line, the information label is pasted on the product, and the product information label and box number label are pasted on the side of the carton, QC inspection stamp.



Voltage & input line
identification

Product information label


2.For single carton packaging, the line label is pasted 80mm away from the end of the line, the information label is pasted on the product, and the product information label and box number label are pasted on the side of the carton, QC inspection stamp.



Voltage & input line
identification

Product information label

3. For wooden case packaging, the line label is pasted 80mm away from the line end, the information label is pasted on the product, and the product information label and box number label are pasted on the side of the carton, QC inspection stamp.



Voltage & input line
identification

Product information label

Name	Size	Quantity / box	Quantity / box	Net weight of single product (kg)	Net weight of each box (kg)	Gross weight (kg)	Outer box size (mm)
Carton	L5000*12*22mm	5m*2	10m	1.18	2.36	2.64	360*360*60
Carton	L5000*12*22mm	5m*8	40m	1.18	5.9	10.56	380*380*265
Wooden case	Customized to order			1.18			

Reliability testing

Test item	Test requirement	Test standard	Test method or condition
Safety regulation test	Mechanical strength	GB-7000.1	Impact hammer 0.7 J
	Dust and water proof test	GB-7000.1	IP67
	Winding test	GB-7000.1	φ150mm wooden disc, 60N tension, 10 times at room temperature, 10 times after cold treatment (-15°C±2°C, 16h)
	Low temperature winding test	GB-7000.1	Winding the winding shaft, low temperature box -c, after 16h, 15 °C± 2 °C winding the winding shaft for 2 turns
	Low temperature impact test	GB-7000.1	Winding the winding shaft, low temperature box -15°C±5°C, after 16h, winding the winding shaft for 2 turns
	Insulation resistance	GB-7000.1	≤ 2MΩ
	Electrical strength	GB-7000.1	500V
Mechanical reliability test	Left and right bending test	Internal standards	With an interval of 200mm (including welding points), the left and right bends are respectively 100 times
	Distortion test	Internal standards	Twist clockwise for 5 turns and then relax. Repeat for 100 times
	Falling test	Internal standards	100 times of wrestling
Environmental reliability test	High temperature storage	GB/T 2423.2	60°C, 168 hours
	Low temperature storage	GB/T 2423.1	-30°C, 168 hours
	High temperature and humidity operation	GB/T 2423.3	60°C, 85%RH
	Salt spray Test	GB/T 2423.17	5% salt solution concentration, 24h
	IK Test	GB/T 20138	Each exposed surface bears 5 impacts
	Normal temperature aging	Internal standards	25°C, 6000 hours
	Switching impulse	Internal standards	10s on, 10s off, 10000 times